

## Fleece

### Synthetic-fibre fleece for waterproofing resins



#### Brief description

Fleece is a synthetic-fibre fleece with a grid print, specially designed for use with WestWood PMMA waterproofing resins. The fleece helps to control the layer thickness when applying waterproofing resins and also has a strengthening and crack-bridging effect in the hardened waterproofing layer.

#### Material

Mechanically strengthened and heat-set synthetic-fibre fleece with a weight per unit area of 110 g/m<sup>2</sup>

#### Properties and advantages

- High tear strength and tear propagation resistance
- High extensibility
- Specially designed for use with WestWood waterproofing resins in terms of material properties, thickness and degree of density
- The 5x5 cm and 10x10 cm grid prints facilitate easy and reliable application of waterproofing with layer thickness control function
- The optimised grid print serves as a cutting and measuring line and significantly simplifies the processing in detail and in the area

#### Areas of application

Fleece is used as reinforcement and to ensure a minimum layer thickness for WestWood waterproofing resins to create high-quality, flexible and crack-bridging waterproofing systems.

#### Pack size

Roll (W x L):



10.50 cm	x	50 m
15.00 cm	x	50 m
20.00 cm	x	50 m
26.00 cm	x	50 m
35.00 cm	x	50 m
42.00 cm	x	50 m
52.00 cm	x	50 m
70.00 cm	x	50 m
105.00 cm	x	50 m

#### Standard colour

White with grey grid print

#### Storage

Store Fleece in a dry place, protected against moisture and dirt, and if possible, in a horizontal position.

#### Product application

A single layer of the fleece is fully saturated with WestWood waterproofing resins when applied. The joints must have an overlap of at least a 5 cm. For further information please refer to the product information sheets for WestWood waterproofing resins.



Product information sheet

## Fleece

Synthetic-fibre fleece for waterproofing resins

### General information

The above information, especially information about application of the products, is based on extensive development work as well as many years of experience and is provided to the best of our knowledge. However, the wide variety of requirements and conditions on site mean that it is necessary for the product to be tested to ensure that it is suitable for the intended purpose. Only the most recent version of the document is valid. We reserve the right to make changes to reflect advances in technology or improvements to our products.

Rev.: 01 April 2026