

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Wecryl 271 2K**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** See Section 16
- **Application of the substance / the mixture** Sealing
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
WestWood Liquid Technologies Limited
31 Morris Road
Nuffield Industrial Estate
Poole, Dorset BH17 0GG
United Kingdom
Fon: +44 800 808 5480
Internet: www.westwood-uk.com
- **Further information obtainable from:**
Product safety department
Mr. Wayne Chissell
Fon: +44 7725 940 678
Email: wayne.chissell@westwood-uk.com
- **Emergency telephone number:**
24h - Emergency number
Phone: +1 872 5888271 (W)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

(Contd. on page 2)

— GB —

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: Wecryl 271 2K

(Contd. of page 1)

- **Signal word** Warning
- **Hazard-determining components of labelling:**
 - 2-ethylhexyl acrylate
 - n-butyl acrylate
 - methyl methacrylate
 - diethanol-p-toluidine
- **Hazard statements**
 - H226 Flammable liquid and vapour.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H335 May cause respiratory irritation.
 - H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P261 Avoid breathing vapours.
 - P280 Wear protective gloves/ eye protection.
 - P312 Call a POISON CENTER/ doctor if you feel unwell.
 - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 - P403+P235 Store in a well-ventilated place. Keep cool.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Does not meet the PBT-criteria of Annex XIII of UK REACH (self assessment).
- **vPvB:** Does not meet the vPvB-criteria of Annex XIII of UK REACH (self assessment).

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 103-11-7 EINECS: 203-080-7 Reg.nr.: 01-2119453158-37	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥10-<25%
CAS: 141-32-2 EINECS: 205-480-7 Reg.nr.: 01-2119453155-43	n-butyl acrylate Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥2.5-<10%
CAS: 80-62-6 EINECS: 202-615-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥2.5-<10%
Reg.nr.: 01-2119979579-10	diethanol-p-toluidine Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-≤0.5%

- **Additional information:**
 - Product does not contain respirable particulate matter. Classification with H373 / H372 does not apply to the preparation.
 - For the wording of the listed hazard phrases refer to section 16.

— GB —
(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: **Wecryl 271 2K**

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Personal protection for the First Aider.
Take affected persons out of danger area and lay down.
Involve doctor immediately.
- **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
Seek medical treatment.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
Irritant to skin, eyes and respiratory system.
- **4.3 Indication of any immediate medical attention and special treatment needed**
On inhaling, also with missing illness signs, give inhalatives Corticoid (e. g. , Ventolair).

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
Steams are more difficult than air.
Creeping steams can lead to the inflammation in a larger distance!
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear fully protective suit.
Wear self-contained respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation



Keep away from ignition sources.

(Contd. on page 4)

— GB —

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: Wecryl 271 2K

(Contd. of page 3)

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· **6.3 Methods and material for containment and cleaning up:**

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient fire. Keep container tightly closed to prevent heat build up (pressure increase). Avoid heat.

Not giving remnants back into the storage vessels.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

at least 7-fold air changes per hour

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Only explosion-proof equipment.

Protect against electrostatic charges.

Protect from heat.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Store in a cool location.

· **Information about storage in one common storage facility:**

Store away from oxidising agents.

Store away from foodstuffs.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Store under lock and key and with access restricted to technical experts or their assistants only.

max. Storage temperature 30 ° C

Storage in a collecting room is required.

Keep container tightly sealed.

Protect from heat and direct sunlight.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 5)

— GB —

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: Wecryl 271 2K

(Contd. of page 4)

· Ingredients with limit values that require monitoring at the workplace:		
141-32-2 n-butyl acrylate (≥2.5-<10%)		
WEL	Short-term value: 26 mg/m³, 5 ppm Long-term value: 5 mg/m³, 1 ppm	
80-62-6 methyl methacrylate (≥2.5-<10%)		
WEL	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm	
112945-52-5 Synthetische, amorphe, pyrogene Kieselsäure (≤2.5%)		
TWA	Short-term value: 6 mg/m³ Long-term value: 2.4 mg/m³	
· DNELs		
103-11-7 2-ethylhexyl acrylate		
Dermal	DNEL	242 µg/cm² (Employee / Industrial / Commercial) Long-term and short-term
Inhalative	DNEL	37.5 mg/m³ (Employee / Industrial / Commercial)
141-32-2 n-butyl acrylate		
Inhalative	DNEL (worker)	11 mg/m³ (Long-term - local effects)
80-62-6 methyl methacrylate		
Inhalative	DNEL (worker)	210 mg/m³ (Long-term - local effects)
		210 mg/m³ (Long-term - systemic effects)
		Long-term
	DNEL (population)	74.3 mg/m³ (Long-term - systemic effects) 105 mg/m³ (Long-term - local effects)
diethanol-p-toluidine		
Dermal	DNEL (worker)	1.4 mg/kg bw/day (Long-term - systemic effects)
Inhalative	DNEL (worker)	9.8 mg/m³ (Long-term - systemic effects)
· PNECs		
103-11-7 2-ethylhexyl acrylate		
Boden	2.3 mg/l (Soil microorganisms) 1 mg/l (ground)	
PNEC	0.0023 mg/kg (oral intake)	
water	0.126 mg/l (sediment) 0.002727 mg/l (freshwater)	
80-62-6 methyl methacrylate		
PNEC sediment	1.47 mg/kg dw (ground) 5.74 mg/kg dw (freshwater)	
PNEC	0.094 mg/l (seawater) 0.94 mg/l (freshwater)	
diethanol-p-toluidine		
PNEC sediment	0.12 mg/kg dw (seawater) 1.2 mg/kg dw (water)	
PNEC	0.005 mg/l (seawater) 0.048 mg/l (water)	

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: Wecryl 271 2K

(Contd. of page 5)

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

· Respiratory protection:

Ensure good ventilation.

In interiors and at transgression of the limiting values breath filtration device: Filter type A1 using an air recycling independent breathing apparatus at high concentrations A2 at an intensive or longer outline.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Check protective gloves prior to each use for their proper condition.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

· Material of gloves



Butyl rubber gloves - butyl e.g. KCL BUTOJET

Recommended thickness of the material: ≥ 0.7 mm

Breakthrough time: ≥ 480 min

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Protective gloves according EN 374.

Suitable material: nitrile.

· Penetration time of glove material

Our Recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR

· Not suitable are gloves made of the following materials: Leather gloves

· Eye protection:



Tightly sealed goggles EN standard: EN 166

(Contd. on page 7)

— GB —

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: **Wecryl 271 2K**

(Contd. of page 6)

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	Different according to colouring after MMA
Odour:	Not determinable.
Odour threshold:	

· pH-value: Mixture is non-polar/aprotic.

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

· Flash point: 37 °C (DIN EN ISO 3680)

· Flammability: Flammable.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Not determined.

· Explosion limits:

Lower:	1.7 Vol % (MMA)
Upper:	12.5 Vol % (MMA, 80-62-6 methyl methacrylate)

· Vapour pressure: Not determined.

· Density at 20 °C: 1.08-1.12 g/cm³ (EN ISO 2811-1)

· Evaporation rate: No data available.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water:

log Pow: 4,29 (2-EHA); (25 °C, OECD 107)
log Pow: 1,38 (MMA)
log Kow 2.38 (25 °C) (BA)

· Viscosity:

Dynamic at 20 °C:	9,000-10,000 mPas (EN ISO 2555)
Kinematic at 20 °C:	8,036-9,259 mm ² /s (EN ISO 2431)

· Solvent content:

Organic solvents:	0 %
VOC (EC)	≥7.7-<7.71 %

Solids content: 62-64 %

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: **Wecryl 271 2K**

(Contd. of page 7)

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** see Section 10.2
- **10.3 Possibility of hazardous reactions**
Exothermic reaction.
Reacts with peroxides and other radical forming substances.
A hazardous polymerization may occur after the exhaustion of the inhibitor.
- **10.4 Conditions to avoid** Avoid heat. Avoid direct sunlight.
- **10.5 Incompatible materials:** Reactions with peroxides and other free-radical generators.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.
- **Additional information:**
Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan to the workplace may be present.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects** There were no toxicological findings to the mixture.
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal	LD50	26,037 mg/kg (rabbit)
Inhalative	LC50/4h	134 mg/l (rat)

103-11-7 2-ethylhexyl acrylate

Oral	LD50	4,435 mg/kg (rat) (BASF-Test)
	LD50	4,435 mg/kg (rat)
Dermal	LD50	7,522 mg/kg (hare)
	LC50	7,520 mg/kg (hare)
	LD50	7,522 mg/kg (hare)

141-32-2 n-butyl acrylate

Oral	LD50	3,150 mg/kg (rat) (BASF-Test)
Dermal	LD50	2,000 mg/kg (rabbit) (sonstiges)
Inhalative	LC50/4h	10.3 mg/l (rat) (OECD 403) steaming blev tests

80-62-6 methyl methacrylate

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
	NOAEL	2,000 ppm (rat) n drinking water, 6-2000 ppm Findings: No toxic effects
Dermal	LD50	>5,000 mg/kg (rat)
	LD50	>5,000 mg/kg (hare)
	LC50	>5,000 mg/kg (rabbit)

(Contd. on page 9)

GB —

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: Wecryl 271 2K

(Contd. of page 8)

Inhalative	LD50	>5,000 mg/kg (hare)
	NOAEL	25 ppm (rat) 25 - 400 ppm Findings: Damage to mucous membranes in the nose at 400 ppm
	LC50/4h	29.8 mg/l (rat)
diethanol-p-toluidine		
Oral	LD50	500 mg/kg (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Irritant effect
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Other information (about experimental toxicology):**
Due to the high vapor pressure is a harmful concentration in the air quickly been reached. At high concentrations can occur narcotic effect.
- **Additional toxicological information:**
- **Toxicokinetics, metabolism and distribution** The drug is metabolized rapidly (MMA).

· Acute effects (acute toxicity, irritation and corrosivity)		
103-11-7 2-ethylhexyl acrylate		
Oral	LD50	4,435 mg/kg (rat)
80-62-6 methyl methacrylate		
Oral	LD50	>5,000 mg/kg (rat)

- **Repeated dose toxicity** no data available
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)** not tested
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity	
103-11-7 2-ethylhexyl acrylate	
EC50/21d	0.5 mg/l (daphnia)
80-62-6 methyl methacrylate	
EC3/16h	100 mg/l (<i>Pseudomonas putida</i>) (Cell proliferation inhibition test, Bringmann-Kühn)
· Aquatic toxicity:	
103-11-7 2-ethylhexyl acrylate	
other (28d)	>1,000 mg/kg (Soil microorganisms) (OECD 217) The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/48h	1.3 mg/l (daphnia)

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: Wecryl 271 2K

(Contd. of page 9)

LC50/96h	1.3 mg/l (daphnia magna) (OECD-Richtline 202) Part 1 1.81 mg/l (fish) 1.81 mg/l (Rainbow trout) (OECD 203)
ErC50/72h	1.71 mg/l (alga)
NOEC/21d	0.19 mg/l (daphnia) 0.19 mg/l (daphnia magna) The details of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/72h (static)	1.71 mg/l (scenedesmus subspicatus) (OECD 201) Die Angaben der toxischen Wirkung bezieht sich auf die analytisch ermittelte Konzentration.
141-32-2 n-butyl acrylate	
EC0/3d other (28d)	>150 mg/l (Bel) (industriell (aerob)) >1,000 mg/kg (BMO) (OECD 217) The product has not been tested. the statement was derived from product b of similar structure or composition. The indication of toxicity refers to the nominal concentration.
EC50/48h	8.2 mg/l (daphnia magna) (OECD-Richtline 202) The indication of toxicity refers to the analytically determined concentration.
NOEC/21d (static)	0.136 mg/l (daphnia magna) (OECD 211) The indication of the toxic effect refers to analytically determined concentrations.
EC50/96h (static)	2.65 mg/l (Selenastrum capricornutum) (OECD 201) The indication of toxicity refers to the analytically determined concentration.
EC20/0,5h	2.1 mg/l (w) (OECD guideline 203, flow rate) The indication of the toxic effect refers to the analytically determined concentration. >1,000 mg/l (Bel) (OECD 209) The product has not been tested. The statement was derived from a similar product structure or composition.
80-62-6 methyl methacrylate	
EC50/48h	69 mg/l (daphnia magna) (OECD 202)
LC50/96h	>79 mg/l (Rainbow trout) (OECD 203)
ErC50/72h	>110 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC/72h	>110 mg/l (Selenastrum capricornutum) (OECD 201)
EC50/72h	>110 mg/l (Selenastrum capricornutum) (OECD 201)
NOEC	9.4 mg/l (Danio rerio) (OECD 210) fish early life stage test, 35 days 37 mg/l (daphnia magna) (OECD 211) 21 days

· **12.2 Persistence and degradability** No further relevant information available.

· **Other information:** The product is easily biodegradable.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil**

MMA: A binding to the solid phase of soil, sediment and sewage sludge is not expected. From the water surface the substance is slowly evaporated into the atmosphere. Where the substance into the environment he verleibt preferably in the compartment into which it has emerged.

2-EHA: The product floats on water and does not dissolve. Adsorption on soil is not likely.

· **Additional ecological information:**

· **COD-value:** 2-EHA: Theoretical oxygen demand (TOD) = 5.6 g/g

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: Wecryl 271 2K

(Contd. of page 10)

- **BOD5-value:** 0.14 g/g (MMA)
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Does not meet the PBT-criteria of Annex XIII of UK REACH (self assessment).
- **vPvB:** Does not meet the vPvB-criteria of Annex XIII of UK REACH (self assessment).
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncured product residues are special waste.
Cured product residues are not hazardous waste.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR, IMDG	Void
· IATA	UN1263
· 14.2 UN proper shipping name	
· ADR, IMDG	Void
· IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG	
· Class	Void
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG	Void
· IATA	III

(Contd. on page 12)

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: Wecryl 271 2K

(Contd. of page 11)

· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Remarks:	> 450 l: 3 F1, III (2.2.3.1.5)
· IMDG	
· Remarks:	> 450 l: 3, III (2.3.2.5)
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· Regulated explosives precursors
None of the ingredients is listed.
· Regulated poisons
None of the ingredients is listed.
· Reportable explosives precursors
None of the ingredients is listed.
· Reportable poisons
None of the ingredients is listed.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **National regulations:**
- **Information about limitation of use:**
Employment restrictions under the Maternity Protection Directive (94/33/EC).
Employment restrictions for maternity Directive (92/85/EEC) for expectant and nursing mothers.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

These figures relate to the product as delivered.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

(Contd. on page 13)

GB —

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version number 3

Revision: 27.03.2025

Trade name: Wecryl 271 2K

(Contd. of page 12)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

· Training hints

Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555).

Instruction must take place before the start of employment and at least annually thereafter.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· Sourceswww.gestis.dewww.echa.eulogkow.cisti.nrc.ca**· * Data compared to the previous version altered.**