

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Wecryl 885 H**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** See Section 16
- **Application of the substance / the mixture** Binder
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 WestWood Liquid Technologies Limited
 31 Morris Road
 Nuffield Industrial Estate
 Poole, Dorset BH17 0GG
 United Kingdom
 Fon: +44 800 808 5480
 Internet: www.westwood-uk.com
- **Further information obtainable from:**
 Product safety department
 Mr. Wayne Chissell
 Fon: +44 7725 940 678
 Email: wayne.chissell@westwood-uk.com
- **Emergency telephone number:**
 24h - Emergency number
 Phone: +1 872 5888271 (W)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

— GB —

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Methyl methacrylate
Bisphenol A epichlorohydrin resins (MG ≤700)
n-butyl acrylate
diethanol-p-toluidine

· Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P280 Wear protective clothing/ eye protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P312 Call a POISON CENTER/ doctor if you feel unwell.
P403+P235 Store in a well-ventilated place. Keep cool.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Does not meet the PBT-criteria of Annex XIII of UK REACH (self assessment).
· **vPvB:** Does not meet the vPvB-criteria of Annex XIII of UK REACH (self assessment).

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 80-62-6 EINECS: 202-615-1 Reg.nr.: 01-2119452498-28	Methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26	Bisphenol A epichlorohydrin resins (MG ≤700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	≥10-<25%
CAS: 141-32-2 EINECS: 205-480-7 Reg.nr.: 01-2119453155-43	n-butyl acrylate Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥2.5-<10%

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 2)

EC number: 911-490-9 Reg.nr.: 01-2119979579-10	diethanol-p-toluidine Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-≤0.5%
---	---	------------

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.
Take affected persons out of danger area and lay down.
Involve doctor immediately.

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
Seek medical treatment.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
Immediately rinse with water.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Skin sensitization.
Irritant to skin, eyes and respiratory system.

· 4.3 Indication of any immediate medical attention and special treatment needed

On inhaling, also with missing illness signs, give inhalatives Corticoid (e. g. , Ventolair).

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:** Carbon dioxide, sand, extinguishing powder, foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
Steams are more difficult than air.
Creeping steams can lead to the inflammation in a larger distance!

· 5.3 Advice for firefighters

· **Protective equipment:**

Wear fully protective suit.
Wear self-contained respiratory protective device.

· **Additional information**

Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

— GB —

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: **Wecryl 885 H**

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation



Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient fire. Keep container tightly closed to prevent heat build up (pressure increase). Avoid heat.

Not giving remnants back into the storage vessels.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

at least 7-fold air changes per hour

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Only explosion-proof equipment.

Protect against electrostatic charges.

Protect from heat.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

· Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

max. Storage temperature 30 ° C

Storage in a collecting room is required.

Store under lock and key and with access restricted to technical experts or their assistants only.

Keep container tightly sealed.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 4)

Protect from heat and direct sunlight.

· **7.3 Specific end use(s)** Building coating or sealing.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**

80-62-6 Methyl methacrylate (50-100%)

WEL Short-term value: 416 mg/m³, 100 ppm
Long-term value: 208 mg/m³, 50 ppm

141-32-2 n-butyl acrylate (≥2.5-<10%)

WEL Short-term value: 26 mg/m³, 5 ppm
Long-term value: 5 mg/m³, 1 ppm

· **DNELs**

80-62-6 Methyl methacrylate

Inhalative	DNEL	208 mg/m ³ (worker)
	DNEL (worker)	210 mg/m ³ (Long-term - local effects) 210 mg/m ³ (Long-term - systemic effects) Long-term
	DNEL (population)	74.3 mg/m ³ (Long-term - systemic effects) 105 mg/m ³ (Long-term - local effects)

25068-38-6 Bisphenol A epichlorohydrin resins (MG ≤700)

Oral	DNEL (population)	0.75 mg/kg bw/day (Short term and long term Systemic)
Dermal	DNEL (worker)	8.3 mg/kg bw/day (Short term and long term Systemic)
Inhalative	DNEL (worker)	12.3 mg/m ³ (Short term and long term Systemic)
	DNEL (population)	0.75 mg/m ³ (Short term and long term Systemic)

141-32-2 n-butyl acrylate

Inhalative DNEL (worker) 11 mg/m³ (Long-term - local effects)

diethanol-p-toluidine

Dermal	DNEL (worker)	1.4 mg/kg bw/day (Long-term - systemic effects)
Inhalative	DNEL (worker)	9.8 mg/m ³ (Long-term - systemic effects)

· **PNECs**

80-62-6 Methyl methacrylate

PNEC	1.48 mg/kg
PNEC sediment	1.47 mg/kg dw (ground)
	5.74 mg/kg dw (freshwater)
	10 mg/l
PNEC	0.094 mg/l (seawater)
	0.94 mg/l (freshwater)

25068-38-6 Bisphenol A epichlorohydrin resins (MG ≤700)

PNEC sediment	0.05 mg/kg dw (sediment)
	0.5 mg/kg dw (seawater)
	0.5 mg/kg dw (freshwater)
	0.3 µg/l (seawater)
PNEC	

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 5)

PNEC	3 µg/l (freshwater) 10 mg/l (sewage plant)
diethanol-p-toluidine	
PNEC sediment	0.12 mg/kg dw (seawater) 1.2 mg/kg dw (water)
PNEC	0.005 mg/l (seawater) 0.048 mg/l (water)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

· **Respiratory protection:**

Ensure good ventilation.

In interiors and at transgression of the limiting values breath filtration device: Filter type A1 using an air recycling independent breathing apparatus at high concentrations A2 at an intensive or longer outline.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Check protective gloves prior to each use for their proper condition.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

General recommendation: The usage time of the protective gloves is approx. 50% of the penetration time measured in the laboratory!

· **Material of gloves**



Butyl rubber gloves - butyl e.g. KCL BUTOJET

Recommended thickness of the material: ≥ 0.7 mm

Breakthrough time: ≥ 480 min

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Protective gloves according EN 374.

Suitable material: nitrile.

· **Penetration time of glove material**

Our Recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 6)

- **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**
Butyl rubber, BR
- **For the permanent contact gloves made of the following materials are suitable:** Butyl rubber, BR
- **Not suitable are gloves made of the following materials:** Leather gloves
- **Eye protection:**



Tightly sealed goggles EN standard: EN 166

- **Body protection:**



Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	unpigmented after MMA
Odour:	
Odour threshold:	Not determined.

- **pH-value:** Not determined.
Mixture is non-polar/aprotic.

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

- **Flash point:** 12 °C (DIN EN ISO 3680)

- **Flammability** Not applicable.
Highly flammable.

- **Auto-ignition temperature:** 430 °C (MMA)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Not determined.

· Explosion limits:

Lower:	1.65 Vol % (MMA)
Upper:	12.5 Vol % (MMA)

- **Vapour pressure:** Not determined.

- **Density at 20 °C:** 1.03 g/cm³ (EN ISO 2811-1)

- **Relative density** Not determined.

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 7)

· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	log Pow: 1,38 (MMA) log Kow 2.38 (25 °C) (BA)
· Viscosity: Dynamic: Kinematic at 20 °C:	Not determined. 11-13 s (ISO 6 mm)
· Solvent content: Organic solvents: VOC (EC)	0 % 3.02 %
Solids content:	40-42 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** see Section 10.2
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Exothermic reaction.
Reacts with peroxides and other radical forming substances.
A hazardous polymerization may occur after the exhaustion of the inhibitor.
- **10.4 Conditions to avoid** Avoid heat. Avoid direct sunlight.
- **10.5 Incompatible materials:** Reactions with peroxides and other free-radical generators.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products used according to specifications.
- **Additional information:**
Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan to the workplace may be present.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects** There were no toxicological findings to the mixture.
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Dermal	LD50	66,335 mg/kg
Inhalative	LC50/4h	342 mg/l (rat)

80-62-6 Methyl methacrylate

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
	NOAEL	2,000 ppm (rat) n drinking water, 6-2000 ppm Findings: No toxic effects

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 8)

Dermal	LD50	>5,000 mg/kg (rat)
	LD50	>5,000 mg/kg (hare)
	LC50	>5,000 mg/kg (rabbit)
	LD50	>5,000 mg/kg (hare)
Inhalative	NOAEL	25 ppm (rat) 25 - 400 ppm Findings: Damage to mucous membranes in the nose at 400 ppm
	LC50/4h	29.8 mg/l (rat)
	25068-38-6 Bisphenol A epichlorohydrin resins (MG ≤700)	
Oral	LD50	>10,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) 23,000 mg/kg (hare)
141-32-2 n-butyl acrylate		
Oral	LD50	3,150 mg/kg (rat) (BASF-Test)
Dermal	LD50	2,000 mg/kg (rabbit) (sonstiges) 2,000 mg/kg (rat) >2,000 mg/kg (hare)
Inhalative	LC50/4h	2,000 mg/kg (rat) >2,000 mg/kg (hare)
		10.3 mg/l (rat) (OECD 403) steaming blev tests
diethanol-p-toluidine		
Oral	LD50	500 mg/kg (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Other information (about experimental toxicology):**
Due to the high vapor pressure is a harmful concentration in the air quickly been reached. At high concentrations can occur narcotic effect.
- **Subacute to chronic toxicity:** not tested
- **Additional toxicological information:**
- **Toxicokinetics, metabolism and distribution** The drug is metabolized rapidly (MMA).

· **Acute effects (acute toxicity, irritation and corrosivity)**

80-62-6 Methyl methacrylate

Oral | LD50 | >5,000 mg/kg (rat)

- **Repeated dose toxicity** no data available
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)** not tested
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 9)

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

80-62-6 Methyl methacrylate

EC3/16h	100 mg/l (Pseudomonas putida) (Cell proliferation inhibition test, Bringmann-Kühn)
EC50/21d	49 mg/l (daphnia)

· Aquatic toxicity:

80-62-6 Methyl methacrylate

EC50	170 mg/l (aquatic algae and cyanobacteria)
EC50/48h	69 mg/l (daphnia)
	69 mg/l (daphnia magna) (OECD 202)
LC50/96h	>79 mg/l (aquatic vertebrates - in vivo)
	>79 mg/l (Rainbow trout) (OECD 203)
ErC50/72h	>110 mg/l (alga)
	>110 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC/72h	49 mg/l (alga)
	>110 mg/l (Selenastrum capricornutum) (OECD 201)
NOEC/21d	37 mg/l (daphnia)
EC50/72h	>110 mg/l (Selenastrum capricornutum) (OECD 201)
EC0	100 mg/l (escherichia coli)
NOEC	9.4 mg/l (Danio rerio) (OECD 210)
	fish early life stage test, 35 days
	37 mg/l (daphnia magna) (OECD 211)
	21 days

25068-38-6 Bisphenol A epichlorohydrin resins (MG ≤700)

LC50	1.5 mg/l (fish)
EC50/48h	1.8 mg/l (daphnia magna)
LC50/96h	3.6 mg/l (Leuciscus idus melanotus)
EC50/96h	220 mg/l (alga)

141-32-2 n-butyl acrylate

EC50	8.2 mg/l (daphnia)
LC50	2.1 mg/l (carp)
EC0/3d	>150 mg/l (Bel) (industriell (aerob))
other (28d)	>1,000 mg/kg (BMO) (OECD 217)
	The product has not been tested. the statement was derived from product b of similar structure or composition. The indication of toxicity refers to the nominal concentration.
EC50/48h	8.2 mg/l (daphnia magna) (OECD-Richtline 202)
	The indication of toxicity refers to the analytically determined concentration.
NOEC/21d (static)	0.136 mg/l (daphnia magna) (OECD 211)
	The indication of the toxic effect refers to analytically determined concentrations.
EC50/96h (static)	2.65 mg/l (Selenastrum capricornutum) (OECD 201)
	The indication of toxicity refers to the analytically determined concentration.

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 10)

EC20/0,5h	2.1 mg/l (w) (OECD guideline 203, flow rate) The indication of the toxic effect refers to the analytically determined concentration. >1,000 mg/l (Bel) (OECD 209) The product has not been tested. The statement was derived from a similar product structure or composition.
NOEC	0.136 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is easily biodegradable.
- **12.3 Bioaccumulative potential**
2-EHA:
Can be accumulated in organisms.
bioaccumulation potential:
Bioconcentration Factor: 282.4 (calculated)
- **12.4 Mobility in soil**
MMA: A binding to the solid phase of soil, sediment and sewage sludge is not expected. From the water surface the substance is slowly evaporated into the atmosphere. Where the substance into the environment he verleiht preferably in the compartment into which it has emerged.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **BOD5-value:** 0.14 g/g (MMA)
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Does not meet the PBT-criteria of Annex XIII of UK REACH (self assessment).
- **vPvB:** Does not meet the vPvB-criteria of Annex XIII of UK REACH (self assessment).
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncured product residues are special waste.
Cured product residues are not hazardous waste.
- **Waste disposal key:**
The following waste codes of the European Waste Catalogue (EWC), are considered a recommendation.
The Disposal must be coordinated with the local waste disposal company.

Liquid product:

080 409 * adhesives and sealants containing organic solvents or other dangerous substances contain.

080 410 adhesives and sealants containing wastes other than those mentioned under * 080 409.

Cured product:

170 203 plastic

(Contd. on page 12)

— GB —

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 11)

· **Uncleaned packaging:**

· **Recommendation:**

This product (liquid) and its container must be disposed of as hazardous waste.
Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT, special provision 640D PAINT
· 14.3 Transport hazard class(es) · ADR	
	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E

(Contd. on page 13)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 12)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions under the Maternity Protection Directive (94/33/EC).
Employment restrictions for maternity Directive (92/85/EEC) for expectant and nursing mothers.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

These figures relate to the product as delivered.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 14)

Safety data sheet according to UK REACH

Printing date 26.06.2025

Version number 4

Revision: 26.06.2025

Trade name: Wecryl 885 H

(Contd. of page 13)

· Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

· Training hints

Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555).
Instruction must take place before the start of employment and at least annually thereafter.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· Sources

www.gestis.de
www.echa.eu
logkow.cisti.nrc.ca

· * Data compared to the previous version altered.