

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Wetraffic 493**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** See Section 16
- **Application of the substance / the mixture** Textured coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
WestWood Liquid Technologies Limited
31 Morris Road
Nuffield Industrial Estate
Poole, Dorset BH17 0GG
United Kingdom
Fon: +44 800 808 5480
Internet: www.westwood-uk.com
- **Further information obtainable from:**
Product safety department
Mr. Wayne Chissell
Fon: +44 7725 940 678
Email: wayne.chissell@westwood-uk.com
- **Emergency telephone number:**
24h - Emergency number
Phone: +1 872 5888271 (W)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: Wetraffic 493

(Contd. of page 1)

Hazard-determining components of labelling:

2-Ethylhexyl acrylate
Methyl methacrylate
diethanol-p-toluidine
Fatty acid, C 18 - unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P280 Wear protective clothing/ eye protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P403+P235 Store in a well-ventilated place. Keep cool.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards
Results of PBT and vPvB assessment

PBT: Does not meet the PBT-criteria of Annex XIII of UK REACH (self assessment).
vPvB: Does not meet the vPvB-criteria of Annex XIII of UK REACH (self assessment).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 103-11-7 EINECS: 238-878-4 Reg.nr.: 01-2119453158-37	2-Ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥2.5-<10%
CAS: 80-62-6 EINECS: 202-615-1 Reg.nr.: 01-2119452498-28	Methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥2.5-<10%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO ₂) STOT RE 1, H372	≥0-≤2.5%
EC number: 911-490-9 Reg.nr.: 01-2119979579-10	diethanol-p-toluidine Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-≤0.5%
CAS: 162627-17-0 Reg.nr.: 01-2119970640-38	Fatty acid, C 18 - unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine Skin Sens. 1, H317	≥0.1-≤0.5%

Additional information:

Classification with H372/ H373 not applicable to the preparation.
The inhalable fine dust is bound in the preparation (liquid).
For the wording of the listed hazard phrases refer to section 16.

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: **Wetraffic 493**

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.
Take affected persons out of danger area and lay down.
Involve doctor immediately.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
Seek medical treatment.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Irritant to skin, eyes and respiratory system.
Skin sensitization.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: Carbon dioxide, sand, extinguishing powder, foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Nitrogen oxides (NO_x)
Carbon monoxide (CO)

· 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.
Wear fully protective suit.

· Additional information

Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation



Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: Wetraffic 493

(Contd. of page 3)

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient fire. Keep container tightly closed to prevent heat build up (pressure increase). Avoid heat.

Not giving remnants back into the storage vessels.

Providing good ventilating/suction at work.

at least 7-fold air changes per hour

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Only explosion-proof equipment.

Protect against electrostatic charges.

Protect from heat.

· 7.2 Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Store in a cool location.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

Storage in a collecting room is required.

Store under lock and key and with access restricted to technical experts or their assistants only.

max. Storage temperature 30 ° C

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) Building coating or sealing.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters**· Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 5)

— GB —

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: Wetraffic 493

(Contd. of page 4)

· Ingredients with limit values that require monitoring at the workplace:			
80-62-6 Methyl methacrylate (≥2.5-<10%)			
WEL	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm		
· DNELs			
103-11-7 2-Ethylhexyl acrylate			
Dermal	DNEL	242 µg/cm² (Employee / Industrial / Commercial) Long-term and short-term	
Inhalative	DNEL	37.5 mg/m³ (Employee / Industrial / Commercial) 38 mg/m³ (human)	
80-62-6 Methyl methacrylate			
Inhalative	DNEL	208 mg/m³ (worker)	
	DNEL (worker)	210 mg/m³ (Long-term - local effects) 210 mg/m³ (Long-term - systemic effects) Long-term	
		DNEL (population)	74.3 mg/m³ (Long-term - systemic effects) 105 mg/m³ (Long-term - local effects)
diethanol-p-toluidine			
Dermal	DNEL (worker)	1.4 mg/kg bw/day (Long-term - systemic effects)	
Inhalative	DNEL (worker)	9.8 mg/m³ (Long-term - systemic effects)	
· PNECs			
103-11-7 2-Ethylhexyl acrylate			
Boden	2.3 mg/l (Soil microorganisms) 1 mg/l (ground)		
PNEC	1 mg/kg 0.0023 mg/kg (oral intake)		
water	0.126 mg/l (sediment) 0.002727 mg/l (freshwater)		
PNEC	2.3 mg/l		
80-62-6 Methyl methacrylate			
PNEC	1.48 mg/kg		
PNEC sediment	1.47 mg/kg dw (ground) 5.74 mg/kg dw (freshwater)		
PNEC	10 mg/l 0.094 mg/l (seawater) 0.94 mg/l (freshwater)		
diethanol-p-toluidine			
PNEC sediment	0.12 mg/kg dw (seawater) 1.2 mg/kg dw (water)		
PNEC	0.005 mg/l (seawater) 0.048 mg/l (water)		

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 6)

— GB —

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: **Wetraffic 493**

(Contd. of page 5)

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In interiors and at transgression of the limiting values breath filtration device: Filter type A1 using an air recycling independent breathing apparatus at high concentrations A2 at an intensive or longer outline.

Ensure good ventilation.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

General recommendation: The usage time of the protective gloves is approx. 50% of the penetration time measured in the laboratory!

Check protective gloves prior to each use for their proper condition.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Protective gloves according EN 374.

Suitable material: nitrile.

· Penetration time of glove material

Our Recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Butyl rubber, BR

· For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR

· Not suitable are gloves made of the following materials: Leather gloves

· Eye protection:



Tightly sealed goggles EN standard: EN 166

(Contd. on page 7)

— GB —

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: **Wetraffic 493**

(Contd. of page 6)

· **Body protection:**


Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Various colours

· **Odour:** Ester-like

· **Odour threshold:** Not determined.

pH-value:	Mixture is non-polar/aprotic. Not determined.
-----------	--

· **Change in condition**

Melting point/freezing point:	Undetermined.
-------------------------------	---------------

Initial boiling point and boiling range:	Undetermined.
--	---------------

Flash point:	25 °C
--------------	-------

Flammability	Flammable. Not applicable.
--------------	-------------------------------

Auto-ignition temperature:	252 °C (103-11-7 2-Ethylhexyl acrylate)
----------------------------	---

Ignition temperature:	Product is not selfigniting.
-----------------------	------------------------------

Explosive properties:	Not determined.
-----------------------	-----------------

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

Vapour pressure:	Not determined.
------------------	-----------------

Density at 20 °C:	1.84-1.96 g/cm ³ (EN ISO 2811-1)
-------------------	---

Evaporation rate	Not determined.
------------------	-----------------

Solubility in / Miscibility with water:	Not miscible or difficult to mix.
---	-----------------------------------

Partition coefficient: n-octanol/water:	Not determined.
---	-----------------

· **Viscosity:**

Dynamic at 20 °C:	13,000 mPas
Kinematic at 20 °C:	6,633-7,065 mm ² /s (EN ISO 2431)

· **Solvent content:**

Organic solvents:	0.1 %
VOC (EC)	≥0.08-<0.14 %

Solids content:	83.5-87.5 %
-----------------	-------------

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: **Wetraffic 493**

(Contd. of page 7)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** see Section 10.2

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions**

Exothermic reaction.

Reacts with peroxides and other radical forming substances.

A hazardous polymerization may occur after the exhaustion of the inhibitor.

· **10.4 Conditions to avoid** Avoid heat. Avoid direct sunlight.

· **10.5 Incompatible materials:** Reactions with peroxides and other free-radical generators.

· **10.6 Hazardous decomposition products:**

No dangerous decomposition products used according to specifications.

· **Additional information:**

Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan to the workplace may be present.

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects** There were no toxicological findings to the mixture.

· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

Quartz sand

Oral	LD50	>1,234,567 mg/kg
	LD50	>1,234,567 mg/kg

103-11-7 2-Ethylhexyl acrylate

Oral	LD50	4,435 mg/kg (rat) (BASF-Test)
	LD50	4,435 mg/kg (rat)
Dermal	LD50	7,522 mg/kg (hare)
	LC50	7,520 mg/kg (hare)
	LD50	7,522 mg/kg (hare)

80-62-6 Methyl methacrylate

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
	NOAEL	2,000 ppm (rat) n drinking water, 6-2000 ppm Findings: No toxic effects
Dermal	LD50	>5,000 mg/kg (rat)
	LD50	>5,000 mg/kg (hare)
	LC50	>5,000 mg/kg (rabbit)
	LD50	>5,000 mg/kg (hare)
Inhalative	NOAEL	25 ppm (rat) 25 - 400 ppm Findings: Damage to mucous membranes in the nose at 400 ppm

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: Wetraffic 493

(Contd. of page 8)

	LC50/4h	29.8 mg/l (rat)
diethanol-p-toluidine		
Oral	LD50	500 mg/kg (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Other information (about experimental toxicology):**
Due to the high vapor pressure is a harmful concentration in the air quickly been reached. At high concentrations can occur narcotic effect.
- **Subacute to chronic toxicity:** not tested
- **Additional toxicological information:**
- **Toxicokinetics, metabolism and distribution** The drug is metabolized rapidly (MMA).

· Acute effects (acute toxicity, irritation and corrosivity)		
Quartz sand		
Oral	LD50	>1,234,567 mg/kg
103-11-7 2-Ethylhexyl acrylate		
Oral	LD50	4,435 mg/kg (rat)
80-62-6 Methyl methacrylate		
Oral	LD50	>5,000 mg/kg (rat)

- **Repeated dose toxicity** no data available
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)** not tested
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity	
103-11-7 2-Ethylhexyl acrylate	
EC50/21d	0.5 mg/l (daphnia)
80-62-6 Methyl methacrylate	
EC3/16h	100 mg/l (Pseudomonas putida) (Cell proliferation inhibition test, Bringmann-Kühn)
EC50/21d	49 mg/l (daphnia)
· Aquatic toxicity:	
103-11-7 2-Ethylhexyl acrylate	
other (28d)	>1,000 mg/kg (Soil microorganisms) (OECD 217) The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/48h	1.3 mg/l (daphnia) 1.3 mg/l (daphnia magna) (OECD-Richtline 202) Part 1

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: Wetraffic 493

(Contd. of page 9)

LC50/96h	1.81 mg/l (aquatic vertebrates - in vivo) 1.81 mg/l (fish) 1.81 mg/l (Rainbow trout) (OECD 203)
ErC50/72h	1.71 mg/l (alga)
NOEC/21d	0.19 mg/l (daphnia) 0.19 mg/l (daphnia magna) The details of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/72h (static)	1.71 mg/l (scenedesmus subspicatus) (OECD 201) Die Angaben der toxischen Wirkung bezieht sich auf die analytisch ermittelte Konzentration.
80-62-6 Methyl methacrylate	
EC50	170 mg/l (aquatic algae and cyanobacteria)
EC50/48h	69 mg/l (daphnia) 69 mg/l (daphnia magna) (OECD 202)
LC50/96h	>79 mg/l (aquatic vertebrates - in vivo) >79 mg/l (Rainbow trout) (OECD 203)
ErC50/72h	>110 mg/l (alga) >110 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC/72h	49 mg/l (alga) >110 mg/l (Selenastrum capricornutum) (OECD 201)
NOEC/21d	37 mg/l (daphnia)
EC50/72h	>110 mg/l (Selenastrum capricornutum) (OECD 201)
EC0	100 mg/l (escherichia coli)
NOEC	9.4 mg/l (Danio rerio) (OECD 210) fish early life stage test, 35 days 37 mg/l (daphnia magna) (OECD 211) 21 days

· **12.2 Persistence and degradability** Easily biodegradable

· **12.3 Bioaccumulative potential**

2-EHA:

Can be accumulated in organisms.

bioaccumulation potential:

Bioconcentration Factor: 282.4 (calculated)

· **12.4 Mobility in soil**

MMA: A binding to the solid phase of soil, sediment and sewage sludge is not expected. From the water surface the substance is slowly evaporated into the atmosphere. Where the substance into the environment he verbleibt preferably in the compartment into which it has emerged.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Does not meet the PBT-criteria of Annex XIII of UK REACH (self assessment).

· **vPvB:** Does not meet the vPvB-criteria of Annex XIII of UK REACH (self assessment).

· **12.6 Other adverse effects** No further relevant information available.

— GB —

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: **Wetraffic 493**

(Contd. of page 10)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.

· Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncured product residues are special waste.

Cured product residues are not hazardous waste.

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

This product (liquid) and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG

Void

· IATA

UN1263

· 14.2 UN proper shipping name

· ADR, IMDG

Void

· IATA

PAINT

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG

· Class

Void

· IATA



· Class

3 Flammable liquids.

· Label

3

· 14.4 Packing group

· ADR, IMDG

Void

· IATA

III

· 14.5 Environmental hazards:

· Marine pollutant:

No

· 14.6 Special precautions for user

Not applicable.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

(Contd. on page 12)

— GB —

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: Wetraffic 493

(Contd. of page 11)

· Transport/Additional information:	
· ADR	
· Remarks:	> 450 l: 3 F1, III
· IMDG	
· Remarks:	> 450 l: 3, III
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· Regulated explosives precursors
None of the ingredients is listed.
· Regulated poisons
None of the ingredients is listed.
· Reportable explosives precursors
None of the ingredients is listed.
· Reportable poisons
None of the ingredients is listed.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **National regulations:**
- **Information about limitation of use:**
Employment restrictions under the Maternity Protection Directive (94/33/EC).
Employment restrictions for maternity Directive (92/85/EEC) for expectant and nursing mothers.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

These figures relate to the product as delivered.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

(Contd. on page 13)

Safety data sheet according to UK REACH

Printing date 09.09.2025

Version number 5

Revision: 09.09.2025

Trade name: Wetraffic 493

(Contd. of page 12)

· Relevant phrases

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

· Training hints

Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555).
Instruction must take place before the start of employment and at least annually thereafter.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· Sources

www.gestis.de
www.echa.eu
logkow.cisti.nrc.ca

· * Data compared to the previous version altered.